
# **Sure-Clamp Access**


## **Rectangular: Unlined**

### **SPECIFICATIONS**

- A. **General Description:** The removable ductwork section features a clamp connection for easy installation and removal. The gasket clamps ensures a secure and tight connection, reducing air leakage and improving overall system performance. When it's time for fire damper inspection the ductwork section can be easily removed and replace without the need for specialized tools, this designed is practical, efficient and takes 50% less time to make mandatory fire damper inspections.
- B. Allowable Leakage: 1/2 CFM per 100 square ft. of ductwork surface area.
- C. Size: 18" X 18" maximum ductwork size
- D. Material: Galvanized ASTM A527
- E. **Liner:** N/A
- F. Flange Connection: 18 GA galvanized sheet metal construction.
- G. **Seams:** Lap and spot weld on 2" interval
- H. Access Section: Length 12" / Minimum 26 Gauge galvanized ASTM A527
- I. **Clamps:** 20 gauge galvanized with zinc coated draw latch. Gasket profile forms to the inside of clamp and seals the outer edges of the ductwork flange.
- J. Gasket: Neoprene gasket 3/16" X 1-1/4"
- K. Seal Seams: In accordance with SMACNA HVAC Duct Construction Standard -Metal and Flexible.
- L. **Installation:** The removable access section shall not be more than 4" away from the fire damper sleeve break away connection. Installing contractor to provide manufacturer with quantity and size for fabrication.
- M. **Manufacturer:** Langdon, Inc.

9865 Wayne Avenue Cincinnati, Ohio 45215 Phone (513) 733-5955






www.langdonsheetmetal.com

ADJUSTABLE DRAW LATCH DETAIL

# ORDER FORM SURE • CLAMP ACCESS



"S"SLIP & "S"SLIP

MATERIAL: 26 GAUGE GALVANIZED

FABRICATE IN ACCORDANCE WITH

LANGDON'S DUCT CONSTRUCTION STANDARDS

MAXIMUM ACCESS SIZE 18" X 18"

<u>TAG</u>	QTY.	<u>END 1</u> (A) (B)	END 2 (C) (D)
<u>EXAMPLE</u>	1	12" X 8"	12" X 8"
		X	X
		X	X
		X	X
		X	X
		X	X
		X	X
		X	X
		X	X

#### www.langdonsheetmetal.com